

Coffee Time Services
Brian Mahoney

9 4 1 - 2 3 2 - 3 7 1 0



Specifications

MODELS

CCLPM-1C and CCLPM-1H

Cabinet Shell:

One piece high-density polyethylene plastic. Resists cracks, fading and yellowing. Color molded into cabinet to hide scrapes caused by rough usage. Cabinet is easily removed for access to interior components.

Frame:

Rigid, non-corroding, plastic base and mid-pan. A metal strut provides support to chassis. The frame design allows for easy maintenance and refurbishment.

Cold Water Reservoir:

Type 304 stainless steel. External copper refrigerant coil. Reservoir insulation is a removable polystyrene jacket. Temperature is controlled by adjustable thermostat.

Refrigeration Unit:

Convection cooled condenser. Internally spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Environmentally friendly R134a refrigerant is controlled by calibrated capillary tube.

Capacity*:

Cooler provides .6 G.P.H. (2.3 L.P.H.) of 50°F (10°C) water when room temperature and bottled water temperature is 90°F (32.2°C).

Hot Tank (CCLPM-1H Only):

Type 304 stainless steel. 500 Watt externally mounted band type heating element can be easily removed without draining the water from the cooler. Storage capacity is 1-1/2 quarts (1.4 liters).

Hot Water Thermostat:

Automatic thermostat factory set at approximately 180°F - 190°F (82°C - 88°C). Hot tank is protected by a heat limiter in the event of a thermostat failure. A hot tank on/off switch located on the shelf is easily accessible from rear. An optional adjustable thermostat is also available at extra cost.

Float System:

Dual mechanical float system controls water level in reservoir. Secondary safety float/valve mechanism activates in case of primary valve failure. Safety system has a manual reset feature.

Electrical:

115 Volts, 60 Hz. Compressor HP: 1/20 full load. Amps: CCLPM-1C 1.2; CCLPM-1H 5.5. Removable three wire service cord and polarized plug furnished.

Cooler Dimensions:

Height: 40.9 in. (103.9 cm.)
Width: 12.8 in. (32.5 cm.)
Depth: 12.6 in. (32.0 cm.)

Net Weights (approx.):

CCLPM-1C: 28.5 lbs. (12.9 kg.)
CCLPM-1H: 30.0 lbs.(13.6 kg.)

Shipping Weights:

CCLPM-1C: 31.5 lbs. (14.3 kg.)
CCLPM-1H: 33.0 lbs. (15.0 kg.)

Shipping Dimensions:

Height: 42.0 in. (106.7 cm.)
Width: 13.3 in. (33.7 cm.)
Depth: 13.5 in. (34.3 cm.)

Limited 5 Year Warranty:

(Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each cooler.

Export Models:

Models available to operate on 230V-50/60 Hz. or 220-240V-50Hz. Models available with DEMKO, NEMKO and CE approvals. (UL and ARI not applicable to export models).

Export Warranty:

One year on the sealed refrigeration system and most component parts.

All specifications subject to change without notice.

Warning: Source water must be potable.



* Capacities are at Standard Rating Conditions of 50°F (10°C) outlet water, 90°F (32.2°C) inlet water and 90°F (32.2°C) ambient air. Certified in accordance with the ARI Self-Contained, Mechanically-Refrigerated Drinking-Water Coolers Certification Program, which is based on ARI Standard 1010-02. UL Listed to U.S. and Canadian Safety Standards.